

CLAIMS

1. A system for injecting a blowing agent into polymeric material within a barrel of a polymer processing apparatus, comprising:

5 a conduit having an inlet connectable to a source of blowing agent and an outlet connectable to a port in the barrel to provide a pathway through which blowing agent flows from the source to the polymeric material within the barrel; and

a flow controlling system including a bypassing passageway fluidly connected to the conduit at a position between the inlet and the outlet, the flow controlling device
10 designed to selectively direct blowing agent flowing from the source to the polymeric material within the barrel, or through the bypassing passageway.

2. The system of claim 1, wherein the polymer processing apparatus includes a screw mounted in the barrel and designed to reciprocate from an accumulation
15 position, in which the screw plasticates polymeric material that accumulates downstream of the screw, and an injection position, in which the screw does not plasticate polymeric material and the accumulated polymeric material is injected through an outlet of the barrel.

3. The system of claim 2, wherein the flow controlling system is designed to direct blowing agent flow from the source through the bypassing passageway when the screw is in the injection position.

4. The system of claim 1, wherein the flow controlling system comprises a valve.

5. The system of claim 4, wherein the valve is positioned at a junction of the conduit and the bypassing passageway and is switchable between a first position directing flow from the source to the barrel and a second position directing flow from the source to the bypassing passageway.

6. The system of claim 4, wherein the flow controlling system further comprises a back-pressure regulator.

7. The system of claim 5, wherein the flow controlling system further comprises a back-pressure regulator located in the bypassing passageway downstream of the valve.

5 8. The system of claim 6, wherein the back-pressure regulator is designed to maintain a back pressure approximately equal to the pressure of the polymeric material proximate the blowing agent port when a screw rotates in the barrel to plasticate the polymeric material.

10 9. The system of claim 7, wherein the back-pressure regulator is designed to maintain a back pressure approximately equal to the pressure of the polymeric material proximate the blowing agent port when a screw rotates in the barrel to plasticate the polymeric material.

15 10. The system of claim 9, wherein the back-pressure regulator is designed to maintain a back pressure of between about 500 psi and 4000 psi.

20 11. The system of claim 1, wherein an outlet of the bypassing passageway opens to atmosphere.

 12. The system of claim 1, wherein an outlet of the bypassing passageway is connected to a recovery container.

25 13. The system of claim 1, wherein an outlet of the bypassing passageway is connectable to the source of blowing agent.

30 14. The system of claim 1, wherein the flow controlling system comprises two valves, a first valve in the conduit downstream of a junction of the bypassing passageway and the conduit, and a second valve in the bypassing passageway downstream of the junction.



15. The system of claim 14, including a controller that switches the first valve to an open position when the second valve is closed, and switches the second valve to an open position when the first valve is closed.

5 16. The system of claim 14, further comprising a back-pressure regulator located in the bypassing passageway downstream of the second valve.

17. The system of claim 15, further comprising a back-pressure regulator located in the bypassing passageway downstream of the second valve.

10

18. The system of claim 1, wherein the flow controlling system comprises a valve in the conduit downstream of a junction of the conduit and the bypassing passageway, and a back-pressure regulator in the bypassing passageway downstream of the junction.

15

19. The system of claim 1, wherein the flow controlling system comprises a shut-off valve, and a fluid pathway distance from the shut-off valve to the port in the barrel is no more than 3 inches.

20

20. The system of claim 19, wherein the fluid pathway distance from the shut-off valve to the port in the barrel is no more than 1 inch.

21. The system of claim 19, wherein the shut-off valve is located essentially adjacent to the port in the barrel.

25

22. The system of claim 21, wherein the flow controlling system further comprises a second valve located in the bypassing passageway downstream of the junction.

30

23. The system of claim 21, wherein the flow controlling system further comprises a second shut-off valve in the bypassing passageway downstream of the



junction and a back-pressure regulator in the bypassing passageway downstream of the second valve.

24. The system of claim 21, wherein the flow controlling system further
5 comprises a back pressure regulator in the bypassing passageway downstream of the junction.

25. The system of claim 21, further comprising a check valve between the
10 shutoff valve and the port.

26. The system of claim 25, wherein the flow controlling system further
15 comprises a second valve located in the bypassing passageway downstream of the junction.

27. The system of claim 25, wherein the flow controlling system further
20 comprises a second shut-off valve in the bypassing passageway downstream of the junction and a back pressure regulator in the bypassing passageway downstream of the second valve.

28. The system of claim 25, wherein the flow controlling system further
25 comprises a back pressure regulator in the bypassing passageway downstream of the junction.

29. The system of claim 1, wherein the flow controller system comprises a shut-
30 off valve, wherein an enclosed volume between the shut-off valve and the port in the barrel is less than 0.50 cubic inches.

30. The system of claim 29, wherein the enclosed volume between the shut-
off valve and the port in the barrel is less than 0.10 cubic inches.

31. The system of claim 1, wherein the flow controlling system comprises a
shut-off valve at least a portion of which is positioned within a bore in the barrel.



32. The system of claim 1, wherein a fluid pathway distance from the bypass valve to the port in the barrel is no more than 5 feet.

5 33. The system of claim 1, wherein a fluid pathway distance from the bypass valve to the port in the barrel is no more than 1 foot.

34. The system of claim 1, wherein the source of blowing agent continuously supplies blowing agent to the inlet of the conduit.

10

35. The system of claim 1, wherein the source of blowing agent supplies blowing agent to the inlet of the conduit at a flow rate of less than about 60 lbs/hour.

36. The system of claim 1, further comprising a metering device associated with the conduit, positioned between the source of blowing agent and the barrel port, the metering device constructed and arranged to control the flow rate of blowing agent supplied to the conduit.

37. The system of claim 36, wherein the metering device controls the mass flow rate of blowing agent supplied to the conduit.

20

38. The system of claim 1, wherein the conduit inlet is connectable to a source of blowing agent that is a gas at ambient conditions.

39. The system of claim 1, wherein the conduit inlet is connectable to a source of blowing agent that is a liquid as delivered to the port in the barrel.

25

40. The system of claim 1, wherein the conduit inlet is connectable to a source of blowing agent that is a supercritical fluid at conditions in the extruder.

30

41. The system of claim 1, wherein the blowing agent comprises carbon dioxide.

42. The system of claim 1, wherein the blowing agent comprises nitrogen.

43. The system of claim 1, wherein the polymer processing apparatus
5 comprises a discontinuous plasticating system.

44. The system of claim 43, wherein the polymer processing apparatus
comprises an injection molding apparatus.

10 45. The system of claim 43, wherein the polymer processing apparatus
comprises a blow molding apparatus.

46. A system for processing polymeric foam material comprising:
an extruder including a barrel and a screw designed to rotate within the barrel to
15 convey polymeric material in a downstream direction within a polymer processing space
between the barrel and the screw, the extruder having a port in the barrel positioned to
introduce a blowing agent into polymeric material in the polymer processing space to
allow formation therein of a solution of polymer and blowing agent; and
a shut-off valve having an inlet fluidly connected to a blowing agent source and
20 an outlet fluidly connected to the port, the shut-off valve designed to selectively permit
or prevent the flow of blowing agent therethrough,
wherein a fluid pathway distance from the shut-off valve to the port in the barrel
is no more than 3 inches.

25 47. The system of claim 46, wherein the shut-off valve is a two-way valve.

48. The system of claim 47, wherein the shut-off valve is switchable between
a first position directing flow of blowing agent from the source to the port, and a second
position directing flow of blowing agent from the source to a bypassing passageway.

30

49. The system of claim 47, wherein a fluid pathway distance from the shut-
off valve to the port in the barrel is no more than 1 cm.

50. The system of claim 47, wherein the outlet of the shut-off valve is located essentially adjacent to the port in the barrel.

5 51. The system of claim 47, wherein an enclosed volume between the shut-off valve and the port in the barrel is less than 0.50 cubic inches.

52. The system of claim 47, wherein an enclosed volume between the shut-off valve and the port in the barrel is less than 0.10 cubic inches.

10 53. The system of claim 47, wherein an enclosed volume between the shut-off valve and the port in the barrel is less than 0.05 cubic inches.

15 54. The system of claim 47, wherein the port in the barrel comprises a plurality of orifices.

55. The system of claim 47, further comprising a blowing agent injection assembly fluidly connected to the source of blowing agent via a conduit, the blowing agent injection assembly including the shut-off valve and having an outlet comprising the port in the barrel.

56. The system of claim 55, wherein the blowing agent injection assembly is positioned within a bore in the barrel.

25 ~~57.~~ A blowing agent injection assembly operable with polymer processing apparatus, comprising an inlet and a multi-orifice outlet, the assembly having an internal passageway connecting the inlet to the multi-orifice outlet, the blowing agent injection assembly including a valve coupled to the passageway, the valve moveable between a first position which permits the flow of blowing agent from the inlet to the outlet through
30 the passageway and a second position which prevents the flow of blowing agent from the inlet to the outlet through the passageway.

58. The blowing agent injection assembly of claim 57, wherein the valve is a two-way valve, wherein the second position directs the flow of blowing agent from the inlet to a bypassing passageway.

59. The blowing agent injection assembly of claim 57, wherein the multi-orifice outlet includes at least 10 orifices.

60. The blowing agent injection assembly of claim 57, wherein the blowing agent injection assembly includes at least a portion of the valve inserted within a sleeve, the sleeve defining the multi-orifice outlet.

61. The blowing agent injection assembly of claim 57, further comprising a back-flow restrictor moveable between an open configuration which permits the flow of blowing agent from the inlet to the outlet through the passageway and a closed configuration which prevents the flow of molten polymeric material from the outlet to the inlet through the passageway.

62. The blowing agent injection assembly, wherein the back-flow restrictor comprises a ball check valve.

63. A method of injecting blowing agent into a barrel of a polymer processing apparatus comprising:

continuously supplying blowing agent from a blowing agent source connected to the barrel of a polymer processing apparatus while discontinuously injecting the blowing agent from the source into the barrel.

64. The method of claim 63, further comprising selectively directing the flow of the blowing agent flowing from the source to the polymeric material within the barrel, or through the bypassing passageway.

65. The method of claim 63, further comprising discontinuously plasticating polymeric material in the barrel.

66. The method of claim 64, further comprising selectively directing the flow of the blowing agent from the source through the bypassing passageway when not plasticating polymeric material in the barrel.

5

67. The method of claim 65, further comprising stopping the plasticating of polymeric material for a time period of less than 15 minutes.

10

68. The method of claim 63, further comprising reciprocating a screw mounted in the barrel between an accumulation mode, in which polymeric material accumulates downstream of the screw, and an injection mode, in which accumulated polymeric material is injected through an outlet of the barrel.

15

69. The method of claim 68, comprising directing the flow of the blowing agent from the source away from the barrel when the screw is in the injection mode.

20

70. The method of claim 64, further comprising maintaining the pressure in a section of the bypassing passageway approximately equal to the pressure of polymeric material in the barrel when a screw rotates in the barrel to plasticate the polymeric material.

25

71. The method of claim 63, comprising continuously supplying blowing agent at a constant flow rate.

72. The method of claim 63, wherein the constant flow rate is less than about 60 lbs/hour.

30

73. The method of claim 63, wherein the constant flow rate is between about 0.001 lbs/hour and 10 lbs/hour.

74. The method of claim 63, further comprising injecting polymeric material from an outlet of the barrel into an injection mold.

1
CL. 26A

75.

polymer processing space between a screw and a barrel;

5

less than 3 inches from the blowing agent port.

10

to the blowing agent port at a location essentially adjacent the blowing agent port.

	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2433	2434	2435	2436	2437	2438	2439	2440	2441	2442	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---